

RS485 to TCP/IP Converter

The 10/100 Mbps TCP/IP Converter Converts the RS 485 Inputs to the TCP Output and Vice Versa.



The RS485 to TCP / IP Converter is a 10/100 Mbps Converter with built – in lightning protection. It has an entry Grommet for the RS 485 receiving socket and TCP/IP OUT on other side. It also has a power input socket. It supports a power supply module having a 220V AC wire plug on one side and a banana pin on the other side which mates into the power socket of the converter. This supply is 5V DC. In addition to these a Green wire will be emanating out of the converter. Care should be taken to ensure that this Green wire is connected to a proper EARTH. If this is not done, the entire advantage of having lightning arrestor circuitry on-board is lost.

Communication Interfaces	
Ethernet Interface	10 / 100 Base Mbps
Serial Interface	RS485 - 2 wire
Baud Rates	1200 to 115 Kbps (Default set to 19200) .
Network Protocols	TCP, IP, ICMP, ARP, Telnet, UDP.
Configuration	Through Ethernet Port, Utility on a PC.
Indications	4 Status LED's for Serial & Ethernet activities.
Modes	Both Master / Slave modes are possible.
Mechanical : Connectors	
RS485	4 way phoenix
Ethernet	RJ45
Dimensions	115 mm X 90 mm X 55 mm
Power Supply	
External Power Supply	5V DC, 350mA regulated
Environmental	
Operating Temperature	0°C to 55°C.
Relative Humidity	10 to 90 % RH non-condensing.

RS485 to TCP/IP Converter



Hardware.. Firmware.. Software - Integrated Solutions

Technical Specification

Voltage requirement	5Vdc (PS module is supplied along with convertor.)
Convertor Input	RS 485
Convertor Output	TCP/IP
Normal current consumption	350 m amps
Operating temperature	0°C to + 55°C (32°F to 131°F)
Relative humidity	90% max, operating non-condensing
Casing	IP65
Status LED	Green & Red
Color	Matt Grey
Warranty Policy	Warranty for 18 months from date of delivery against defective workmanship

© Copyright 2010 Electron India. All rights reserved. No part of this publication may be reproduced or transmitted in any form or for any purpose without the express permission of Electron India. The information contained herein may be changed without prior notice. JAVA and Slumberger are registered Trademark of their respective owners.

Electron India

ISO 9001: 2008 Certified

Type-II, Unit No: 9, Dr V.S.I Estate,
Thiruvanmiyur, CHENNAI – 600 041
☎ +91 (44) 22541392, 22542517.
Fax +91 (44) 22541803.
E-mail: email@electronindia.com
URL: www.electronindia.com

